

- ★FUEL DISPENERS
- \*ADBLUE DISPENERS
- **★CHARGING PILE**
- **★INDUSTRIAL PUMP**
- ★MOBILE CONTAINER FUELING STATION
- **★ELECTRONIC PARTS**
- **★MECHANICAL PARTS**
- \*TANK GAUGING SYSTEM
- ★FUEL MANAGEMENT SYSTEM



# HONGYANG

# COMPANY INTRODUCTION



Hongyang Group is specializing in research, design and production of fuel dispenser, LPG,CNG,LNG and fuel-related equipment. It has more than 500 working staff and an area of 26000 m2. Since its founding in 1992, it has gained dozens of certificates, either domestically or internationally. The products have well accepted in more than 60 countries and area, such as South-east Asia, Africa, Middle East and South America.

# COMPANY STRUCTURE



Hongyang Group is the one and only fuel dispenser and fuel—related equipment maker in China, which has been designing its own electronic, mechanical, and forecourt management system. The R&D and production of the whole electronic, mechanical and software are in the same factory, so it is easy and effective for quality control and management.

R&D
department | Complete R&D department with electronic, software, mechnical, sheet metal CAD









# ABOUT US

Production Department

Modern workshop, comprehensive equipment, integrated production, it's a sole manufacturer of mechanical parts and electronic components together in China.









Quality management Department

Strict quality inspection and management









Purchasing Department

Accountant Department

Sales Department

After-Sales Department









# FUELING STATION SHOW




















# W2 series FUEL DISPENSER



### TECHNICAL PERFORMANCE

Flow rate	$55\pm5$ (L/min), or $85\pm5$ (L/min)
Meter Accuracy	±0.3 %
Noise	≤72db
Horizontal suction distance	50m
Vertical suction distance	6m
Single or three	AC220V/50Hz,0.75kw or
Phase Motor	AC380V/50Hz,0.75kw
Input Voltage	AC 220V /50 Hz or AC 380V /50 Hz
Electronic	Liter range: 0.01~999999.99
Counter	Sale Range:0.01~999999.99
	Unit Price range:0.01~9999.99
	Totalizer range:0~999999999
Environmental	Temperature:-40°C ~+50°C
Condition	Humidity: 5% ~95%
Presetting function	Preset sale or volume
Data Storage	More than 10 years
Flexible Pipe	Included, 1.5" pipe
Hose	4.5m black,oil resistant





- Model
  - $\star$  W2 series CMD I 6875K-G (Suction type, I Product, I Nozzle, I Flowmeter , I keypad, 2 displays)
- Packing Size
  - ★ I O50\*460\* I 750mm (Length\*Thickness\*Height)
  - ★ 55 Sets in one 40 ft HQ container

#### Model With Same Size

- W2 Series CMD | 6875K-G22 (Suction type, | Product, 2 Nozzle, 2 Flowmeter, 2 keypad, 2 displays)
   Submersible type fuel dispenser is available
- Printer,LED Rolling display(Optional)



#### Model

\*W2 series CMD | 6875K-G22 (Suction type, | 2 Product, 2 Nozzles, 2 Flowmeters, 2 keypads, 2 displays)

- Packing Size
  - 1050\*460\*1750mm (Length\*Thickness\*Height) \*55 Sets in one 40 ft HQ container
- Submersible type fuel dispenser is available
- Printer,LED Rolling display(Optional)



### TECHNICAL PERFORMANCE

Flow rate	$55\pm5$ (L/min), or $85\pm5$ (L/min)
Meter Accuracy	±0.3 %
Noise	≤72db
Horizontal suction distance	50m
Vertical suction distance	6m
Single or three Phase Motor	AC220V/50Hz,0.75kw or AC380V/50Hz,0.75kw
Input Voltage	AC 220V /50 Hz or AC 380V /50 Hz
Electronic	Liter range: 0.01~999999.99
Counter	Sale Range:0.01~999999.99
	Unit Price range: 0.01 ~ 9999.99
	Totalizer range:0~99999999
Environmental	Temperature:-40°C ~+50°C
Condition	Humidity: 5% ~95%
Presetting function	Preset sale or volume
Data Storage	More than 10 years
Flexible Pipe	Included, 1.5" pipe
Hose	4.5m black,oil resistant





#### Model

★W2 series CMD I 6875K-GA (Suction type, I 2 Product, 2 Nozzles, 2 Flowmeters, 2 keypads, 4 displays)

# Packing Size

1050\*460\*1750mm (Length\*Thickness\*Height)
\*55 Sets in one 40 ft HQ container

### Submersible type fuel dispenser is available

Printer,LED Rolling display(Optional)

